CALIBER TURF COMPANY

SPECIFICATION SHEET
Revision 2026-10-12

Tour Master

Putting green / multi-functional

FROM THE PRODUCT SHEET

- Texturized PE yarn system for professional performance
- Field & olive green bi-color surface for a natural look
- Built for multi-functional use with durable UV stability

Face weight	Pile height	Total weight
58 oz per sq yd	**16** mm ±2 mm (≈0.63 in)	**85** oz per sq yd

Clean & safe · Anti-UV · Putting green · Soft · Natural look · Great resilience · All weather · Low maintenance

GENERAL

Application	Putting green / multi-functional
Color	Field & olive green bi-color
Accreditations	Professional

YARN

Structure	Texturized
Composition	PE
Dtex	6,000
Yarn thickness	330 ±20 µm
Yarn width	1.5 ±0.1 mm

TURF

Total weight	85 oz per sq yd
Face weight	58 oz per sq yd
Pile height	16 mm ±2 mm (≈0.63 in)
Gauge	3/16 in
Density	84,000 ±100 stitches per sq m

BACKING

Primary backing	PP + PP
Backing weight	5.90 oz/sq yd
Latex weight	22.1 oz/sq yd ±10%
Carpet tuft withdrawal	≥40 N

ROLLS

Roll width	4.57 m / 4.0 m / 2.0 m (15 ft / 13.1 ft / 6.6 ft)
Roll length	On request
Yarn color fastness	Grey scale ≥4

PERFORMANCE & INFILL

UV stability	>5,000 hrs
Water permeability	>2,000 mm/hr
Strands per tuft	8
Stitches per 10 cm	40 ±1
Infill particle size range	0.315–0.8 mm
Infill particle shape	Round
Infill bulk density	1.28 g/cm³
Infill application rate	12 kg/sq m

Caliber Turf Company 4526 Bronze Way, Dallas, TX 75236 (469) 949-2003 info@caliberturf.com caliberturf.com
Sales and pickup: Monday to Friday 7:00 am to 4:00 pm · Saturday 7:30 am to 12:00 pm · Sunday closed

Values as printed on the current product sheet, units and tolerances included. Turf is priced by inquiry. Trade only: Caliber supplies contractors and installers.